

**ITEM NUMBER :** SHIPA10W-40SLCF

### PRODUCT DESCRIPTION

It is a semi-synthetic engine oil designed to meet the lubrication needs of both naturally aspirated and turbocharged engines by blending synthetic and high-quality base oils with advanced additives. It is suitable for use in all gasoline, diesel, and LPG-powered passenger cars and light commercial vehicles.

### KEY FEATURES AND CUSTOMER BENEFITS

- Reduces oil consumption by maintaining optimal viscosity.
- Prevents ash and deposit buildup in the engine with special additives.
- Enhances performance and prolongs engine life by keeping key parts clean while protecting against corrosion and wear.
- Forms a strong oil layer on engine parts in all weather conditions and temperatures, reducing wear during start-up and warm-up.

### APPROVALS

- API SL/CF
- ACEA A3/B4
- MB 229.1
- VW 501.00/505.00
- RN0710

### KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 10W-40
Pour Point, °C, ASTM D97	-32
Flash Point, Cleveland Open Cup, °C, ASTM D92	214
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	91
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.5-16.3
Density @ 15 C, g/ml, ASTM D4052	0,87
Viscosity Index, ASTM D2270	140

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

### **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

### **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

### **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

### **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)