

ITEM NUMBER : SHIPA15W-40SLCF

PRODUCT DESCRIPTION

It is a high-performance engine oil designed for different driving conditions, providing excellent protection and lubrication. Made by blending mineral base oils with special additives, it ensures reliable engine performance.

KEY FEATURES AND CUSTOMER BENEFITS

- Full protection against engine corrosion and wear.
- Excellent wear control with minimal sludge buildup, ensuring smooth flow across a wide temperature range.
- Made for all types of gasoline, diesel, and LPG engines, including naturally aspirated or turbocharged engines in passenger cars and light commercial vehicles.

APPROVALS

- API SN/CF
- ACEA A3/B3/B4

KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	102
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.5-16.3
Density @ 15 C, g/ml, ASTM D4052	0,871
Viscosity Index, ASTM D2270	130

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com