

**ITEM NUMBER :** SHIPA20W-50SLCF

### PRODUCT DESCRIPTION

It is a high-performance engine oil designed for all seasons, offering excellent protection and lubrication. Made with high-quality mineral base oils and special additives, it is ideal for gasoline, LPG, diesel, and light commercial vehicles.

### KEY FEATURES AND CUSTOMER BENEFITS

- Helps prevent sludge buildup and deposits.
- Keeps engines clean and extends the life of components.
- Offers excellent stability, maintaining viscosity for consistent performance.
- Reduces oil consumption and wear.
- Provides a strong oil layer that ensures full lubrication in all driving conditions and temperatures.

### APPROVALS

- API SL/CF

### KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 20W-50
Pour Point, °C, ASTM D97	-28
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	173,2
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	16.3-21.9
Density @ 15 C, g/ml, ASTM D4052	0,891
Viscosity Index, ASTM D2270	120

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

### **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

### **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

### **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

### **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)