

ITEM NUMBER : SHIMOT10W-40SLCF

PRODUCT DESCRIPTION

This high-quality 4-stroke motorcycle oil is made by blending mineral and synthetic oils with special additives. It is specially designed for high-performance motorcycles.

KEY FEATURES AND CUSTOMER BENEFITS

- Protects the engine from rust, wear, and foam buildup.
- Forms a strong oil layer at all temperatures, reducing wear when starting and warming up the engine.
- Works well in all weather and road conditions, making it safe to use all year. In winter, its low viscosity helps the engine start easily and reduces wear.

APPROVALS

- API SL/CF
- JASO MA2
- APITC

KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 10W-40
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	221
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	89,3
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.5-16.3
Density @ 15 C, g/ml, ASTM D4052	0,865
Viscosity Index, ASTM D2270	140

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com