

ITEM NUMBER : SHIMOT15W-50SLCF

PRODUCT DESCRIPTION

Power Protection Formula 4T is specially made for riders who love motorcycling. SHINDO BAIKU 4T 15W-50 SL/CF is a high-quality, advanced engine oil for 4-stroke motorcycles. It helps protect the engine from harmful deposits that can reduce its power.

KEY FEATURES AND CUSTOMER BENEFITS

- Helps the engine maintain its original power even after long, fast, and high-temperature rides.
- Keeps the engine clean, ensuring consistent power protection until the next oil change.
- Specially formulated to protect clutches and gears.
- Suitable for engines with catalytic converters.

APPROVALS

- API SL/CF
- JASO MA2
- JASO MA
- API TC

KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 15W-50
Pour Point, °C, ASTM D97	-27
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	139
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	16.3-21.9
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	130

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com