

**ITEM NUMBER :** SHITRA-ATFDCT

### PRODUCT DESCRIPTION

It is a high-performance synthetic transmission oil made by blending synthetic base oils with advanced additives. It is designed for use in passenger cars and light commercial vehicles with dual-clutch transmissions (DCT).

### KEY FEATURES AND CUSTOMER BENEFITS

- With advanced additives, it reduces transmission wear and helps extend its lifespan.
- Its excellent slip stability forms a lasting film on metal surfaces, reducing wear during gear shifts.
- With high resistance to oxidation and heat, it allows for longer oil change intervals and lowers maintenance costs.
- Its smooth flow and strong wear resistance ensure smooth shifting without interruptions in torque during gear changes.

### APPROVALS

- BMW Drivelogic 7-speed (Getrag) / DCTF-1 BMW 6-speed DCT / BMW MTF LT-5 Chrysler Powershift 6-speed Ford / Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A Mitsubishi TC-SST 6-speed / MZ320065 / DiaQueen SSTF-1 Peugeot / Citroen DCS 6-speed Renault EDC 6-speed / EDC-7 / Talisman R7D Volvo powershift 6-speed VW (Audi, Seat, Skoda) 6-speed VW / Audi TL 52 529 / G 052 529 / DSG7 = S-Tronic 7 VW (Audi, Seat, Skoda) 7-speed VW / Audi TL 521 82 / G 052 182

### KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF DCT
Pour Point, °C, ASTM D97	-45
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	41
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	6.5-8
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	170

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

### **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

### **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

### **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

### **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)