

ITEM NUMBER : SHITRA-ATFCVT

PRODUCT DESCRIPTION

It is a high-performance, fully synthetic transmission oil designed to deliver optimal performance in passenger cars with a variety of continuously variable transmissions (CVT).

KEY FEATURES AND CUSTOMER BENEFITS

- Increased torque capacity
- Enhanced wear protection at the belt-pulley interface
- Better efficiency with a lower chance of belt slipping
- Offers improved resistance to oxidation with excellent viscosity control

APPROVALS

- BMW Mini Cooper EZL 799A; Chery CVT; Daihatsu AMMIX CVTF DFE; Dodge / Jeep / Chrysler NS-2; Dodge / Chrysler / Jeep / Mopar CVT+4; GM /Saturn DEX-CVT / GM CVT; Honda HMMF / HCF2 / CVT; Hyundai / Kia CVT-1 / SP III; Mazda JWS 3320; MG Rover EM-CVT; Mini Cooper EZL 799 / EZL 799A / ZF CVT V1; Mitsubishi CVTF-J1 / CVTF-J4 ve -J4+ / SP-III / CVTF ECO J4; Nissan KTF-1 / Nissan NS-1 / NS-2 / NS-3; Subaru iCVT / Subaru iCVT F / FG; ECVT; NS-2; Suzuki CVTF TC / CVTF 3320 / CVTF 4401 / NS-2; Suzuki CVT Green 1 / Green 2 / Green 1V; Toyota CVTF TC / CVTF FE; Volvo CVT 4959; VW / Audi TL 521 16 (G052 516) / TL 521 80 (G 052 180 A2)

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF CVT
Pour Point, °C, ASTM D97	-48
Flash Point, Cleveland Open Cup, °C, ASTM D92	205
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	38
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.5-8
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	179

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com