

**ITEM NUMBER :** SHIPA0W-30SPCF

### PRODUCT DESCRIPTION

It's a high-quality multi-grade motor oil made with a modern low-friction additive system for top engine protection, even in tough driving conditions. It works better than regular motor oil, reduces friction and wear during start-up, and helps prevent sludge and varnish build-up that can hurt engine performance. The 0W-30 SP is perfect for turbocharged and high-performance cars, trucks, SUVs, and other mobile or stationary engines. It's suitable for vehicles like TOYOTA, LEXUS, HONDA, NISSAN, MAZDA, SUZUKI, MITSUBISHI, CHRYSLER, CHEVROLET, HYUNDAI, KIA, GM, MERCEDES-BENZ, VOLKSWAGEN, and more.

### KEY FEATURES AND CUSTOMER BENEFITS

- Reduces wear with its outstanding flow performance during the engine's first startup, even in cold temperatures.
- Offers strong protection against corrosion and wear.
- Prevents wear by forming a long-lasting oil film in the engine at all temperatures, thanks to its high viscosity index.
- Delivers superior engine protection by preventing the buildup of soot and deposits with its powerful cleaning properties.

### APPROVALS

- API SP
- SN PLUS/SN
- ILSAC GF-6A
- GM DEXOS II
- MB 229.3, 229.5
- VW 502/ 505

### KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 0W-30
Pour Point, °C, ASTM D97	-41
Flash Point, Cleveland Open Cup, °C, ASTM D92	221
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	51,3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	9.3-12.5
Density @ 15 C, g/ml, ASTM D4052	0,842
Viscosity Index, ASTM D2270	171

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

**STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

**HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

**CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

**PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)