

ITEM NUMBER : SHITRA-ATFWS

PRODUCT DESCRIPTION

It is a fully synthetic low-viscosity fluid for automatic transmissions, made with high-quality synthetic oils and special additives. It is specifically designed for the latest AISIN-Warner automatic transmissions in Toyota and Lexus vehicles.

KEY FEATURES AND CUSTOMER BENEFITS

- High viscosity index guarantees reliable performance in all conditions and reduces friction.
- Special additives protect against corrosion, oxidation, foaming, and build-up of deposits.
- Reduces friction across a wide temperature range, ensuring smooth gear shifts.

APPROVALS

- Toyota/Lexus/Scion Type D-II, Type T, T-III, T-IV , Volkswagen/Audi G 052 025 A2/ G 052 055/ G 052 162 (-A1, -A2)/ G 052 533/G 052 990 (A2)/ G 055 025 (A2)/ G US 000 162 , Mitsubishi ATF-J2, SP, P/N MS991156 SP-II, SP-III BMW/MINI P/N 81229400272/2750, 83220024359, 83220026922, 83220402413, 83220403248, 83220403249, 83227542290, 83229407765, 83229407807, Hyundai/KIA SP-II, SP-III, P/N 040000C90SG, UM040 CH2O Red-1 , Nissan/Infinity 402, Matic-D/-J/-K/-W, Mercedes/Daimler MB 236.10/11/3/5/6/7/8/9/9.1, Mazda F-1, Type T-IV, JWS3317, M-5, P/N XT-9-QMM5, M-III

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF WS
Pour Point, °C, ASTM D97	-45
Flash Point, Cleveland Open Cup, °C, ASTM D92	195
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	37,4
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.4-8.9
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	145

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com