

ITEM NUMBER : SHITRA-ATFLT711

PRODUCT DESCRIPTION

A high-performance automatic transmission fluid designed for long-lasting performance in vehicle transmissions.

KEY FEATURES AND CUSTOMER BENEFITS

- Offers balanced additives for smooth gear shifting.
- Helps extend transmission life.
- Reduces friction in the outer rings, improving fuel efficiency in vehicles with automatic transmissions.
- High viscosity index ensures stable performance across a wide temperature range, protecting the transmission and ensuring proper hydraulic steering operation.
- Suitable for use in all seasons.

APPROVALS

- PEUGEOT/CITROEN AUTOMOBILES B71 2340, VOITH TURBO H55.6336.XX, ZF TE-ML 04D, ZF TE-ML 11B, ZF TE ML 14B, ZF TE-ML 17C, MB APPROVAL 236.11

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF LT711
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	200
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	38,1
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.8
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	170

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com