

**ITEM NUMBER :** SHITRA-AFTDEXII**PRODUCT DESCRIPTION**

Automatic transmission fluid made by blending highly refined base oils with special additives. It is designed for use in automatic transmissions, power steering, and certain hydraulic systems in passenger cars and heavy vehicles.

**KEY FEATURES AND CUSTOMER BENEFITS**

- Reduces wear on automatic transmissions and enhances performance with special additives.
- Long-lasting due to their thermal stability and high resistance to oxidation.
- Prevents sediment buildup and foaming, thanks to the special additives.
- Protects gears from rust and corrosion, delivering excellent performance in both hot and cold climates.

**APPROVALS**

- GM DEXRON II-D
- GM DEXRON II-E
- GM TYPE A SUFFIX A

**KEY PROPERTIES AND SPECIFICATIONS**

Grade	ATF DEXRON II
Pour Point, °C, ASTM D97	-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	200
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	38,1
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	6.5-8
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	160

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

### **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

### **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

### **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

### **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)