

ITEM NUMBER : SHITRA-AFTDEXIII

PRODUCT DESCRIPTION

It is a high-performance synthetic automatic transmission fluid made by blending high-quality synthetic base oils with special additives. Developed primarily for automatic transmissions in passenger and heavy-duty vehicles, it is also suitable for use in hydraulic steering systems.

KEY FEATURES AND CUSTOMER BENEFITS

- Provides excellent lubrication with stable viscosity, even at very low temperatures.
- Long service life, thanks to high thermal and oxidation stability, helps reduce operational costs by extending oil change intervals.
- Its superior anti-wear properties protect transmission components and extend transmission life.
- Ensures smooth gear changes with excellent lubrication and friction control, providing a better driving experience.

APPROVALS

- ALLISON C-4 /FORD MERCON V /GM DEXRON III-H/ MAN 339 Type V2 /MAN 339 Type Z2/ MB 236.9 /VOITH H55.6336.XX Volvo 97341 /ZF TE-ML 04D, 05L, 14B, 16L, 20B, 21L, 25B

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF DEXRON III
Pour Point, °C, ASTM D97	-45
Flash Point, Cleveland Open Cup, °C, ASTM D92	195
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	39
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.4-8.9
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	145

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions: info@shindooil.com