

ITEM NUMBER : SHITRA-AFTDEXIV

PRODUCT DESCRIPTION

It is a high-performance universal ATF that offers superior oxidation control, extended service intervals, and reliable performance in both low and high temperatures year-round. It improves fuel economy and provides excellent stability under various driving conditions.

KEY FEATURES AND CUSTOMER BENEFITS

- Excellent performance at low temperatures due to its superior viscosity.
- High oxidation resistance and thermal stability ensure long oil change intervals, reducing maintenance costs and preventing aging.
- Special additives minimize wear in automatic transmissions and extend their lifespan.
- Prevents sediment buildup and foaming with the help of special additives, offering protection against corrosion.

APPROVALS

- GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, VI • Ford MERCON®, MERCON® LV, Acura ATF-Z1 , Audi 5 HP LT71141 , Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4, Allison C-3, C-4, TES-295, TES-389 ,CAT TO-2, Daewoo LT 71141 ,Esso LT 71141, BMW, Honda Z-1, Hyundai/Kia SP-II/III/IV, JASO, FIAT T-IV type, JWS 3309, Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24 , ISUZU BESCO ATF-II /III , Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1 , MINI COOPER T-IV, Opel (all vehicles) , Peugeot ZF 4HP20 , Mercedes, Mitsubishi, Nissan/ Infinity Matic Fluids, Toyota ATF D-II/D-III/T-III/T- IV/WS ,VW 5 HP, G-055-025 A2 (JWS 3309) ,Porsche ZF 5HP19FL, ZF 5HP20, LT71141, Saab T-IV , Scion (all vehicles) ,Shell 3403, M115, LA 2634 , Subaru ATF, Suzuki ATF, Vickers M2950-S, I-286-S, Voith, Volvo CE 97340, ZF all 3 & 4

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF DEXRON IV
Pour Point, °C, ASTM D97	-45
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	40,4
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	5.9
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	148

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com