

ITEM NUMBER : SHITRA-AFTDEXVI**PRODUCT DESCRIPTION**

It is a high-performance synthetic automatic transmission fluid made by blending synthetic base oils with advanced additives. Designed for use in next-generation transmissions of passenger and light commercial vehicles, it is especially suitable for the automatic transmissions of new-generation vehicles from Far Eastern automakers.

KEY FEATURES AND CUSTOMER BENEFITS

- Excellent performance at low temperatures due to its superior viscosity.
- High oxidation resistance and thermal stability offer exceptional aging resistance, extending oil change intervals and reducing maintenance costs.
- Special additives minimize wear in automatic transmissions, helping to extend transmission life.
- Prevents sediment buildup and foaming, while offering protection against corrosion.

APPROVALS

- ALLISON C-4 ATF LT 71141 BMW / MINI P/N 83 22 2 289 720 FORD MERCON LV / P/N XT-6-QSP / DSP [SP] Chrysler / Dodge / Jeep +4 GM DEXRON VI GM DEXRON IIIH / IIIG / IIE / IID / TASA Honda DW-1 / Z-1 / ATF Type 3.0 / ATF Type 3.1 Hyundai / Kia Genuine ATF / SP-II / SP-III / SP-IV / SPH-IV / SP-IV-RR Isuzu ATF / ATF-II / ATF-III JASO M315 Class 1A Mazda FW 6A EL / FW 6AX EL / FZ / JWS 3317 / M-5 / M-III / Type- IV MB 236.5 / 6 / 7 / 8 / 9 / 10 / 11 / 12 / 41 Mitsubishi ATF-J2 / ATF-J3 / SP / SP-II / SP-III Nissan Matic Fluid D / J / K / S / W Subaru HP Suzuki 3314 / 3317 Toyota Type T / D-II / T-III / T-IV / WS (JWS 3324) Volkswagen / Audi G 060 162 (A1, A2, A6) / G 052 162 (-A1, -A2) / G 055 540 (A2) VOLVO P/N 1161521 / 1161540 / 1161640 ZF TE-ML 11A / 11B

KEY PROPERTIES AND SPECIFICATIONS

Grade	ATF DEXRON VI
Pour Point, °C, ASTM D97	-45
Flash Point, Cleveland Open Cup, °C, ASTM D92	215
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	38
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.5
Density @ 15 C, g/ml, ASTM D4052	0,85
Viscosity Index, ASTM D2270	158

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions: info@shindooil.com