

**ITEM NUMBER :** SHIPA5W-30SPCF**PRODUCT DESCRIPTION**

ILSAC GF-6 is a fully synthetic low-viscosity oil designed for top engine performance and protection. Its formula has been updated to meet the higher demands of modern gasoline engines and to comply with the API SP and ILSAC GF-6 standards. It is recommended for use in all vehicles that require SAE 5W-30 engine oil for any driving conditions.

**KEY FEATURES AND CUSTOMER BENEFITS**

- It helps improve fuel efficiency due to its low viscosity and better viscosity stability.
- With its excellent thermal and oxidation stability, it keeps performing well throughout the longest oil change intervals recommended by the vehicle makers.
- Offers strong protection against engine rust and wear.
- Protects against wear during engine start-up, even in the coldest temperatures, thanks to its enhanced viscosity stability.

**APPROVALS**

- API SP
- ILSAC GF-6
- DEXOS 2
- GM 6094M
- CHRYSLER MS-6395M

**KEY PROPERTIES AND SPECIFICATIONS**

Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	69,3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	9.3-12.5
Density @ 15 C, g/ml, ASTM D4052	0,861
Viscosity Index, ASTM D2270	166

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

## **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

## **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

## **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

## **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)