

ITEM NUMBER : SHIPA10W-30SMCF

PRODUCT DESCRIPTION

SHINDO RODO 10W-30 SM/CF is engineered with advanced cleansing technology. It provides superior protection compared to regular motor oils by actively preventing dirt and sludge buildup while also helping to reduce engine noise.

KEY FEATURES AND CUSTOMER BENEFITS

- Helps prevent the formation of harmful engine sludge.
- Designed with advanced cleaning technology.
- Reduces oil evaporation, helping to lower oil consumption.
- Dampens vibrations and decreases engine noise.

APPROVALS

- API SM/CF
- ACEA A2/B2

KEY PROPERTIES AND SPECIFICATIONS

Grade	SAE 10W-30
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	72
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.3-12.5
Density @ 15 C, g/ml, ASTM D4052	0,862
Viscosity Index, ASTM D2270	150

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

STORAGE

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

HEALTH & SAFETY

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

CAUTION

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

PROTECT THE ENVIRONMENT

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:
info@shindooil.com