

**ITEM NUMBER :** SHIPA10W-40SNCF**PRODUCT DESCRIPTION**

It is a synthetic engine oil designed to fulfill the lubrication needs of both naturally aspirated and turbocharged engines by combining premium base oils with advanced additives. This oil is formulated to meet the lubrication demands of gasoline, light diesel, and LPG-powered vehicles.

**KEY FEATURES AND CUSTOMER BENEFITS**

- Increases engine lifespan by reducing wear, even during daily driving.
- Ensures continuous lubrication in all weather and road conditions.
- Suitable for gasoline, diesel, and LPG engines.
- Enables quicker engine start-up and rapid protection.
- Improves fuel efficiency and helps keep the engine clean.

**APPROVALS**

- API SN/CF
- ACEA A3/B4
- MB 229.1, 229.3
- RN0700/0710
- PSA B71 2300
- VW 501.00/505.00

**KEY PROPERTIES AND SPECIFICATIONS**

Grade	SAE 10W-40
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	86,4
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.5-16.3
Density @ 15 C, g/ml, ASTM D4052	0,87
Viscosity Index, ASTM D2270	160

The listed key properties are based on production tolerances and are not a specification. Variations that don't affect performance may occur during manufacturing and blending. Information is subject to change without notice.

### **STORAGE**

It should be kept away from direct sunlight and rain. The packages must be stored in a sealed condition, preferably under a shelter or in an indoor space. The ideal storage temperature range is between (+5)°C and (+40)°C.

### **HEALTH & SAFETY**

When used correctly for its intended purpose and with proper personal hygiene practices, this product is not expected to pose any major health or safety risks. For more detailed information, please refer to the Material Safety Data Sheet (MSDS), which can be obtained upon request from your local sales office.

### **CAUTION**

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly. Do not ingest. If swallowed, seek medical attention immediately.

### **PROTECT THE ENVIRONMENT**

Dispose of used oil at an authorized collection center. Follow local regulations. Do not release into drains, soil, or water.

You can always contact our Technical Help Desk engineers on lubricants and services related questions:  
[info@shindooil.com](mailto:info@shindooil.com)